



Boom Barrier (GA-BB100)

Description: Automatic Boom Barrier (4mts-6mts retractable Arm)
Model No : GA-BB100

Key Features

- Maximum Boom Length up to 6mtr (With Retraceable Feature)
- Aluminium Boom in 75/80mm OD
- Opening Time: 3-6 Second
- Power Supply: 230V
- With IP55 protection grade
- Duty Cycle 100%
- Operating Temp:-10°C to +60°C
- Colour RAL2002

Technical Specifications

- Boom Size:4-6 MTR (Telescopic)
- Frequency : 50/60Hz
- Net Weight : 60KG
- Open Time : 3-6 Second
- Motor: Electro Mechanical
- Voltage : 220v ±10%
- Controller : Microprocessor Based

- Body: Weather Proof with anti corrosion treatment
- Other Accessories: Operating Switch & Boom Stand / Remote
- Interface : RS 485 / TCP/IP
- Boom Motion: Control By Balanced Spring System
- Remote Distance : 10 ~20mtr
- Optional Access Control System: RF Reader, RS 485 to RS 232 Convertor, Photo Cell

Suite No-09, H-15, Ground Floor Sector-63
Noida, Uttar Pradesh - 201301
0120 - 4332193, www.golfautomation.co.in
sales@golfautomation.co.in