



Full Height Turnstile (GA-FHT-1000D)

Description : Full Height Dual Lane Turnstile
Model No : S-FHT-1000D

Key Features

- Access gate mechanic consist by two parts: frame and core. single reading device would be install on the frame, mail parts of core include motor, main board ,shift of the controller, fix poles, turnstiles supporting, turnstile, protection cover, fence, etc.
- Access direction: single or double direction (optional).prohibiting opposite direction passing, one side reading the card, the one side will lock when you passing forcely.
- Self resetting function the system will cancel the people passing right when reading the card but not passing.
- Prohibiting opposite direction passing
- Automatic function of opening or closing when the power off
- Direction indicator function ,showing passing or prohibiting for the people.
- Control board with counting function, LED digital display function (optional)
- Control board with memory function, can meet the groups pass through
- Without time delay require of the control signal thanks to adopt optical hole focus technology

Technical Specifications

- Height: 2215 MM
- Power voltage: Ac220±10%, 50Hz
- Open angle: 90°
- Work Mechanism: Electromechanical with Bi-Directional
- Drive voltage: AC12V+AC18V
- Pass speed: X30 Person/minutes
- Frequency: 50 Hz
- Operation condition: -15°C – +70°C
- Structure: MS/SS 304
- Relative humidity: None-condensation
- Open direction: Single and Double(optional)
- Input signal: 12v DC level or 12v pulse>100ms
- Work environment: Indoor & outdoor (Canopy)
- Working Current: ≤2000mA
- IP Degree: IP66
- Length of the bar:600mm(optional)
- Width of passage: ≤630mm
- Service life : ≥6million
- Arm Design: Four Arm

Suite No-09, H-15, Ground Floor Sector-63
Noida, Uttar Pradesh - 201301
0120 - 4332193, www.golfautomation.co.in
sales@golfautomation.co.in