



Boom Barrier (GA-BB200F)

Description : Automatic boom barrier
Model No : GA-BB200F

Key Features

- Maximum Boom Length up to 5mtr (With Retractable Feature)
- Aluminium Boom in 75/80mm OD
- Opening Time: 3-6 Second
- Power Supply: 230V
- Motor Capacity 240W
- With IP55 protection grade
- Duty Cycle 100%
- Operating Temp:-10°C to +60°C
- Colour RAL2002

Technical Specifications

- Boom Size : Upto 5mtr
- Frequency : 50Hz
- Open Time : 6 ~ 6 sec
- Motor : Electro Mechanical
- Voltage : 220v \pm 10%
- Controller : Microprocessor Based
- Motor Load : 80-90W
- Body : Weather Proof with anty corrosion treatment
- Other Accessories : Operating Switch & Boom Stand
- Interface: RS 485
- Boom Motion : Control By Balanced Spring System
- Boom Movement : Left / Right side (Inter Changeable)
- Remote Distance : 10~20 Mtr
- Optional Access Control : RF Reader, RS 485 to RS 232 Converter, Photo Cell
- Daily Cycle : 100%
- IP Grade : IP 55
- Operating Temp : -10° C ~ 60° C

Suite No-09, H-15, Ground Floor Sector-63
Noida, Uttar Pradesh - 201301
0120 - 4332193, www.golfautomation.co.in
sales@golfautomation.co.in