



## Flap Barrier (GA-FB2000S)

**Description :** Dual Core Bridge Flap Barriers  
**Model No :** GA-FB2000S

### Key Features

- Cabinet & Internal Structure is in 304 SS grade.
- Flap Material is in Acrylic
- Unlock Time 0.6 second
- Passing Speed 30-40 Person/Min.
- Passing Width 500-600mm Per Lane
- Power Supply AC220, 50Hz
- Humidity 95%
- Operational Voltage Motor (24V)
- Working Temp -10°C to +60°C
- Dimension Excluding Bars (H980xW300xD1200mm)

### Technical Specifications

- Outside Housing Material : 304 stainless steel
- Internal Structure : 304 Stainless steel Cover
- Communication port : Weigand/RS485/RS232
- Power voltage: AC220 ± 10%, 50Hz
- Drive Motor : DC motor 24V/40W
- Relative humidity : ≤ 95%, None-condensation
- Open : direction of flap Double
- Gate opening/closing time: 0.6 Second

- Working Current : ≤ 2000 mA
- IP Degree : IP55
- Length of the bar : 260mm
- Width of passage : ≤600 mm
- Pass speed: 30 ~40 Person / Minutes
- Dimension : 1200\*300\*980mm
- Operation condition : -10°C ~ 60°C