



2MP IP Bullet Color IP

Description : Network Bullet Camera with Color Night Vision
Model No : GA-2-BIP-C

Key Features

- 2 MP CMOS Sensor
- 3.6mm Fixed Lens
- White LED Range 15-20m
- H.265+/H.265/H.264 Video Compression
- POE Supported

Technical Specifications

- System Structure: Embedded RTOS design, dual core 32 bits DSP(Hi3516EV100), pure hardware compression
- Sensor: 2MP CMOS(SC2236), color 1.0 Lux@F1.2, B/W 0.1 Lux@F1.2; integrate IR-CUT drive, support linkage control between sensor & IR-CUT& photosensitive& LED fill light, support day/night switch
- Video Process: H.265+/H.265/H.264 video coding, support dual stream, AVI format; code stream 200-8000kpbs adjustable; support PAL and NTSC
- Frame Rates: 2MP @25FPS, support 7-20 FPS adjustable
- Image Output: Main Stream: 1920×1080, 1280×960, 1280×720; Sub Stream: 800×448, 640×480, 640×360, 352×288
- Network Interface: 1*RJ45 Ethernet interface, 10/100M self-adaption, 8KV anti-static electric capacity; support RTSP / DHCP / NTP / ONVIF, GB/T28181 and so on network protocols
- LED: 3 Warm White LED
- Business Functions: Configure by WEB, OSD(on screen display), real-time video transmission, motion detection and support remote surveillance client software(Seetong); support mobile monitoring(iPhone, Android)
- Power Supply (POE): "DC12V power input interface, 115mW power consumption, front end power input, light protection, anti-static, anti-inverse connect, support 18V turn off voltage protection
- Work Conditions: Minus 20°C—+60°C