



3MP IP Dome

Description : 3MP Dome Cameras w 3.6mm fixed lens

Model No : GA-3-DIP

Key Features

- Resolution up to 3MP(2304X1296@25fps)
- Built-in AI humanoid detection algorithm
- Support low bit rate and low latency
- H.265 efficient compression, saving bandwidth and storage space

- Support Smart IR range up to 30 mtrs, infrared autoexposure at night
- ICR infrared filter-type automatic switching for real day and night monitoring
- Support POE power supply function
- Support 3D digital noise reduction, support DWDR
- Support automatic electronic shutter function to adapt to different monitoring environments
- Support Back Light Compensation
- Support ONVIF, SLINK protocol
- Support White Balance and IRIS Control
- Change the password when the initial device is powered on to ensure password security

Technical Specifications

Camera

- Sensor 1/2.8", 3MP progressive scan ultra-low illumination CMOS sensor
- Lens Type 3.6mm Fixed Lens
- Day and Night Mode ICR Switch, Automac / Color / Black and White / External Trigger
- Signal to Noise >52 dB
- WDR DWDR (Off / Low / Medium / High)
- Minimum Illumination 0.01Lux @ F1.2, 0 Lux at IR on
- Auto Gain Control On/ Off
- Electronic Shutter Speed 1/3 to 1/10000 (sec)
- Image Setting Brightness / Contrast / Sharpness / Saturation/ Chroma/3D NR/Mirror
- AI Humanoid Detection
- Responding Speed ≤1s
- Maximum Detection Frame Rate 5fps/s (Color Image)
- Detection Area Support specified area, default full screen
- Shielded area Support 4 areas Setting
- Upload Method Private protocol upload
- Trigger Method Video Trigger

Interface

- Network Interface RJ45 10M/100M network adaptive
- Power DC12V / POE , Max 7W Power Consumption
- General
- IP Rating IP66
- Operating Temperature -20°C – 55°C
- Working Humidity 0%-90%
- Certification BIS, CE, FCC, RoHS

Video Coding

- Video Coding Standards H.265/H.264
- Coding Characteristics Main stream: 2304X1296 @25fps;
- Sub stream: 720X576 @25fps
- Max.Image Resolution 2304X1296
- Video Bit Rate Fixed bit rate, Variable bit rate (1280kpbs-4Mbps)
- Video Type Composite stream / video stream

Network Function

- Network Protocol TCP/IP,UDP,HTTP,DHCP,RTSP,NTP,HTTPS
- Interface Protocol ONVIF
- Number of Simultaneous Preview Videos 5
- Safe Mode Authorized username and password, AES connection encryption, RTSP authentication
- Motion Detection Set detection area, mul-level sensitivity can be set
- Privacy Masking Support 5 area occlusion blocks
- Intelligent Analysis AI Humanoid Detection
- Event Linkage Snapshot, audio output linkage
- Mobile Monitoring Support IOS and ANDROID phone monitoring
- Character Overlay (OSD) Title, Time and date overlay, OSD color optional
- System Upgrade Support remote upgrade of search tools

Suite No-09, H-15, Ground Floor Sector-63
Noida, Uttar Pradesh - 201301
0120 - 4332193, www.golfautomation.co.in
sales@golfautomation.co.in