



2 MP IP PTZ

Description : HD-IP IR high Speed Dome Camera

Model No : GA-2PRZ-150

Key Features

- Support P2P function
- 7" Body Construction, Ip66
- Optional function: POE, TF Card Slot(No TF Card)
- ONVIF Compliant
- Intelligent IR illumination & power consumption is variable, dependant the zoom factor

Technical Specifications

- Solution: 1/2.8" CMOS 2MP Hi3516E+Sony327
- Output Pixel: 1920×1080@30fps / 1920×1080@25fps
- Lens: 36X f=4.6mm~165mm
- BLC: Support
- AGC: Auto/manual
- WB: Auto/manual/indoor/outdoor
- DNR: 2DNR,3DNR
- WDR: DWDR
- S/N Ratio: ≥50dB
- Auto Control IR LED: PWM
- LEDs: Up to 150M
- IR distance: 6PCS IR LEDs+2PCS Laser LEDs
- Communications Protocol: TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
- Communications Protocol: H.265/H.264/M-JPEG
- Software Control: IE, CMS, Management Platform, P2P
- Rotation range: Pan:0~360°, Tilt:0~93°
- Rotation speed: Pan:0~200°/s , Tilt:0~100°/s
- Auto Flip: Horizontal 180°, Vertical 93°
- Preset Points: 220pcs presets (dwell time 01-60s interval available)
- A-B scan: User programmable (scan speed 1-64 levels setting available)
- Guard Tours: 3 groups(Max.16 points, dwell time user selectable)
- Operating temperature: -40°C~+60°C
- Power: DC 12V 4A / PoE(802.3at)
- Consumption: ≥25W
- Lightning Protection: Transient voltage 6000V
- Related Validation: IP66, CE, FCC, RoHS

Suite No-09, H-15, Ground Floor Sector-63
Noida, Uttar Pradesh - 201301
0120 - 4332193, www.golfautomation.co.in
sales@golfautomation.co.in